H75 and H75+



The H75 is a compact drinking water unit designed to be mounted under the sink.

The H75+ was made with home coffee connoisseurs in mind; it includes a precision blending valve and in-line TDS monitor so users can customize TDS profile to their desired needs. This is a must-have feature for users who want the best tasting coffee from their home brewer or espresso machine. This is also a great feature for users who want to add some minerals to their drinking water.

Includes 3-gallon tank and your choice of Stainless-Steel or Brushed Nickel faucet. More details found on the specification sheet on the reverse side.

Our systems are 100% designed and hand built by Living Water in California.

Price H75: \$395 including tax. H75+: \$595 including tax Additional costs for installation



805-915-8040 email: info@livingwatersocal.com website: www.livingwatersocal.com



H75 and H75+



Features

- 75GPD Reverse Osmosis Home System
- Finishing filter balances pH
- High efficiency GRO membrane provides an industry leading 1:1 product-to-waste ratio
- Precision needle valve allows for custom TDS profile (H75+ only)
- Includes built-in TDS monitor (H75+ only)

Applications

- Drinking Water
- Home Espresso Machines, Brewers (H75+ only)

Specifications

- Model number: H75, H75+
- Capacity (GPD): 75GPD Min*
- Membrane: 75GPD TLC
- ► Flow Rate: 2GPM
- Dimensions (Unit Only): 17"H x 15"W x 5"D
- Tank dimensions: 11"D x 15.5"H

*95 GPD tested at 120ppm product and 350ppm feed

Operating Parameters

- Feed Water: Municipal
- Feed Pressure: 40-80psi
- Max Total Dissolved Solids: 2000ppm
- Max Hardness: 15 grains
- pH Range: 3-10